



Rev: NOV 2017

RECOMMENDED INEX>FLOOR CLEAR SEALING SYSTEMS APPLICATION GUIDE

EPIMAX Clear Sealing System is recommended for application **INEX>FLOOR**. This guide provides recommended EPIMAX products and the link for the application guide details to achieve a clear sealed finish to **INEX>FLOOR** for internal and external application of smooth side and rough side.

Products recommended are from the EpiMax range of Coatings and Floor Protection Systems (www.epimax.com.au). EpiMax can be contacted at 1300 721 522.

EpiMax is continually reviewing recommendations based on development work with **INEX>FLOOR**.

We will update our recommendations as we develop new products and application techniques.

SYSTEM SELECTION

APPLICATION	SURFACE	SYSTEM
INTERNAL	SMOOTH and ROUGH	<ul style="list-style-type: none">• EpiMax - 777UHD GLOSS Finish or MATT Finish• Application details are in the following link: https://www.epimax.com.au/solutions/inex-flooring-solutions
EXTERNAL	SMOOTH	<ul style="list-style-type: none">• EpiMax - 777UHD GLOSS Finish or MATT Finish• Application details are in the following link: https://www.epimax.com.au/solutions/inex-flooring-solutions
EXTERNAL	ROUGH	<ul style="list-style-type: none">• EpiMax - 900 GLOSS Finish or SATIN Finish• Application details are in the following link: https://www.epimax.com.au/solutions/inex-flooring-solutions

Please Note: With pre-registration, EpiMax will offer a 12 Month Product Warranty.