

Specification

Product descriptions

Decolife Interior Matt is silicone modified acrylic matt finish, suited to Interior wall applications. Decolife Interior matt is **highly breathable** and with excellent light dispersion that helps to hide surface regularities and minimizes tiger stripes when viewed from oblique angles. Colors appear rich and true with excellent purity.

Decolife has a low odour and contributes to air quality. Decolife has low environmental impact, containing less than 1 gram per litre of VOC (Volatile Organic Compounds) allowing the classification Zero VOC.

Decolife is a high opacity product requiring only one coat to achieve coverage in like colour repaints. In new work just **1 basecoat and 1 topcoat is required**

Product Information

Finish	Matt <2%@600
Density	1.4-1.5g/cm ³
VOC	<1g/L
Temperature Range*	10C – 30C
Clean Up	Water
Packaging	15 Litre Pail

Key Benefits

- Hydrophobic
 - Superior Resistance/ water
 - Vapor & Gas Permeable - Breathable.
 - Self Cleaning Effects.
 - Prevents deterioration resulting from the freeze thaw cycle.
 - Low VOC - (after tinting) Non-hazardous and non-toxic.
-

Warranty

15 years against cracking, peeling & blistering where the product has been applied according to manufacturers displayed directions and in accordance with AS 2311 - the painting of building

Specification

Colour

Si-Rex03 may be tinted to 10,000+ colours using ASF tinting system. These tinters are Zero VOC and **APEO1 free** and will not contribute to the VOC of the base product after tinting. Please note that only **inorganic pigments** will provide lightfast performance in interior applications.

Safety

Refer to product Label and product MSDS 73-101

1 APEO Free

New Surface Preparation

Surfaces to be painted must be clean, smooth, dry and free of contaminants, including dirt, grease, dust, mould & mildew.

For priming use the Decolife to spot or patch new Gyprock or plaster board

Non mineral/ cementitious substrates such as timber, should be primed with Underprep primer

Application

	Method	Theoretical Coverage	Typical DFT	Touch Dry*	Re-Coat*
PRIMER					
Decolife	Spot primer patching/ fillers	12m ² /L	N/A	15 Mins	30 Mins
FIRST COAT					
Decolife	Roller, Brush Spray	12m ² /L	25um	30 Mins	2 hour
TOPCOAT					
Decolife	Roller, Brush Spray	12m ² /L	25um	30 Mins	2 hour

*Note: The information presented is intended as a guide only and is correct to the best of our knowledge at the time of publication. It should not be considered as a definitive approval for suitability for a particular purpose. Specification details may change without notice .

1 APEO (Alkylphenol ethoxylate) is a degradation product which is very toxic to aquatic organisms. It is not easily degradable and has a tendency to bioaccumulation.